

# STBT4

## Suretime 2 Hour Electronic Boost Timer

### Features & Benefits

- Typical applications - Immersion Heaters - Room Heaters - Towel Rails - Lighting
- Various Boost Options
- Automatic timer countdown for up to 2 hours.
- Cancellation of countdown time by pressing the boost button mid-cycle.
- Bright illumination of the boost button at all times.
- Minimalist and simple to use!
- LED indicators for approximate time left on countdown.
- Ideal for immersion control systems not racking up a huge bill.
- Fits a standard flush or surface BS wall box with 25mm depth.



### Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Surface
Earth Class Rating	Class II
Operating Temperature	0°C to 45°C
Ingress Protection Rating	IP20
Setting Type	Button Press
Back Box Minimum Depth (mm)	25
Push Buttons	Yes (Boost Button)
Mounting Hole Centres (mm)	60

# Data sheet

## STBT4

Time / Immersion & General Purpose Timeswitches

<b>Standby Consumption</b>	<1W
<b>Number of Channels</b>	1
<b>Switch rating</b>	13A Resistive, 80W LED, 1000W Halogen, 500W Fluorescent, 100W Low Energy Lighting
<b>Shortest Switching Time</b>	15 Minutes
<b>Time Delay Range</b>	15 Min, 30 Min, 1 Hour, 2 Hours
<b>Permanent ON Facility</b>	No
<b>Multiple Unit Support</b>	No
<b>Cable Entry(s)</b>	Back Entry, Bottom Entry

### General

<b>Weight (g)</b>	113
<b>Height (mm)</b>	85
<b>Width (mm)</b>	85
<b>Depth (mm)</b>	31
<b>Body Construction</b>	Polycarbonate
<b>Product Colour</b>	White
<b>Accessories (Included)</b>	Screws
<b>EAN Number</b>	5012483015285
<b>Guarantee Period</b>	2 Years
<b>Trade Tariff Commodity Code</b>	8536508090

# Data sheet

## STBT4

Time / Immersion & General Purpose Timeswitches

### Line Diagrams

